

NEW

Subli-Flock



XP3121-A3 XP3120-A4 XP2055-ROLL

General Use

Subli-Flock has been manufactured for printing using sublimation inks and is suitable for application to, cotton & poly/cotton. Subli-Flock can be used with the Ultragraphics cutter or with any sublimation system.

Using Subli-Flock

- Print Images and template onto sublimation paper (XP4072a/73a).
- Set heat press to 200°C for 30-35 seconds.

Position the sublimation paper onto the Subli-Flock print side face down with application paper on the top & bottom to protect the press bed.

- Press the Subli-Flock for 30-35 seconds under a medium pressure.
- Once the Subli-Flock has been pressed remove the sublimation paper immediately while still hot.
- Refer to the Xpres Ultragraphics manual for help in using the Subli-Flock in conjunction with the cutter.
- Remove transfers from backing after cutting.
- Apply transfer onto garment at 170°C for 10 seconds.

Technical

- Machine wash 80°C.
- Do not use harsh or bleaching washing materials.
- If ironing is required only iron inside out on reverse of the transfer.

The Sellers and Manufacturers maximum obligation shall be to replace any paper that has been proven to be defective. Neither the Seller nor the Manufacturer of Subli-Flock shall be liable for any injury, direct or consequential, arising out of the use of, or inability to use this paper.



TEL: 01332 855085 FAX: 0800 9808082
Technical Support: 01332 858333
Oakridge Park, Trent Lane
Castle Donington,
Derbyshire DE74 2PY.