



INSTRUCTION & INFORMATION

NYLO PRINT

XP3009A 50cm wide x 25m

Nylo Print is a gloss PVC product which produces full colour transfers for application to 100% nylon products.

50cm & 75cm samples are available free of charge upon request.

STEP BY STEP

STEP 1

Print your design on the smooth matt side (**Do not mirror image**). Allow to dry for 2 hours.

STEP 2

Weed away any excess material.

STEP 3

Place transfer face down onto the garment cover with a silicone sheet and press for 15 seconds at 165°C.

STEP 4

Once pressed, remove the silicone sheet and peel hot.

MICRONS

150

FINISH

GLOSS

TACK

NO

PEEL

HOT

PU OR PVC

PVC

PRODUCT INFORMATION

SIZE:	50cm wide x 5m & 25m rolls
CUTTING FORCE:	Film Blade * (Roland: from 75gf / Mimaki: from 65gf)
APPLICATION TAPE:	Standard or Universal
DRYING TIME:	2 hours

SUITABLE FOR

UNCOATED NYLON

ACCREDITATIONS



PRINT SETTINGS

Refer to 'Textile Transfer Print Settings' sheet.

TRANSFER SETTINGS

TIME	15 seconds
TEMP	165°C
PRESSURE	Medium
PEEL	Hot or Cold

CARE INFORMATION

WASH UP TO 30°C INSIDE OUT

DO NOT DRY CLEAN

DO NOT TUMBLE DRY

DO NOT IRON

STORAGE (Store vertically in a dry room between 15-30°C)

* All force testing has been undertaken using a NEW film blade on a Roland SP300I and a Mimaki CJV150-75. The force will increase with the age of the blade, therefore always test prior to use.

PLEASE NOTE: The sellers and manufacturers maximum obligation shall be to replace any product that has been proven to be defective. Neither the seller nor the manufacturer of Nylo Print shall be liable for any injury direct or consequential, arising out of the use of, or inability to use this range. Nylo Print has been tested using Kustom Kit garments, when applying to other garment brands results may vary, testing prior to purchase is recommended.



Web: www.xpres.co.uk Support www.xprestechnical.co.uk

Oakridge Park, Trent Lane, Castle Donington, Derby DE74 2PY Phone: 01332 855 085 E-mail: sales@xpres.co.uk