

PRINT SETTINGS

Xpres Printable Media - Profiles available to download from downloads.xpres.co.uk

	EVOLUTION PRINT	SOLVENT DARK TURBO	EASY PRINT	SUPERFLEX PRINT	SOLVENT DARK PLUS	SOLVENT LIGHT	SUBLI BLOCK SOFT TURBO	SUBLI BLOCK	POLI-PRINT MONO	BANNER
DRYING TIME	2 Hours	2 Hours	4 Hours	2 Hours	2 Hours	2 Hours	2 Hours	4 Hours	24 Hours	12 Hours
ROLAND - VERSAWORKS										
ECOSOL MAX										
SP300i / SP540i (CMYK)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
BN-20 (CMYK + MT)*	✓	✓	✓	✓	✓	✓		✓	✓	
ECOSOL MAX 2										
SP300i / SP540i (CMYK)										
BN-20 (CMYK + MT)*										
ECOSOL MAX 3										
SP300i / SP540i (CMYK)					NOT RECOMMENDED	NOT RECOMMENDED				
BN-20 (CMYK + MT)*					NOT RECOMMENDED	NOT RECOMMENDED				
TRUEVIS 2										
SG2-300 / SG2-540 (CMYK)	✓	✓	NOT RECOMMENDED	✓	NOT RECOMMENDED	✓	✓	NOT RECOMMENDED	✓	✓
MIMAKI - RASTERLINK										
SS21										
CJV150 (CMYK)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
ES3										
CJV150 (CMYK)	✓	✓	✓	✓	✓	✓	✓		✓	✓

RECOMMENDATIONS:

For optimum print output it is highly recommended by the manufacturer to store the printable media vertically in the original packaging when not in use additionally, store in the same location as the printer for 24 hours prior to printing, in order for the media to acclimatise to the environment.

The drying time is the minimum period of time between printing and using the product, as recommended by the manufacturers.

*BN20 drying time is recommended at 12 hours due to the absence of an in-built heater & dryer.

PLEASE NOTE: The above information is provided as a guide and has been compiled through extensive testing and consultation with the manufacturers of the printable media. Due to a number of factors that surround the printing process Xpres recommends profile testing prior to purchase of our printable media.



Web: www.xpres.co.uk Support www.xprestechnical.co.uk

Oakridge Park, Trent Lane, Castle Donington, Derby DE74 2PY Phone: 01332 855 085 E-mail: sales@xpres.co.uk