

SOLVENT DARK TURBO

XP3085 50cm wide · XP3086 75cm wide

Solvent Dark Turbo is the lightweight printable media that will considerably improve your production. With a rapid pressing time of just 3 seconds, applying vibrant full colour transfers onto light and dark textiles has never been faster!

50cm & 75cm samples are available free of charge upon request.

STEP BY STEP

STEP 1

Print your design on the smooth matt side (**Do not mirror image**). Allow to dry for 2 hours.

STEP 2

Weed away any excess material. Cover the transfer with high tack application tape and using a hard squeegee, using heavy pressure, remove any air bubbles. Turn over and peel the backing away.

STEP 3

Place transfer face up onto the garment (application tape on top) cover with a silicone sheet and press for the time and temperature required.

STEP 4

Once pressed, remove the silicone sheet and take the garment off the heat press. Wait a few seconds then peel warm.

| MICRONS | FINISH | TACK | PEEL | PU OR PVC |
|---------|--------|------|------|-----------|
| 100 | MATT | YES | WARM | PU |

PRODUCT INFORMATION

| | |
|--------------------------|---|
| SIZE: | 50cm & 75cm wide x 25m rolls |
| CUTTING FORCE: | Film Blade* (Roland: from 90gf / Mimaki: from 85gf) |
| APPLICATION TAPE: | High tack application tape |
| DRYING TIME: | 2 hours |

SUITABLE FOR

COTTON
POLYESTER
POLY/COTTON
UNCOATED NYLON

TRANSFER SETTINGS

| | | | |
|------------------------|------------------------|----------------|-------|
| TIME & TEMP | Cotton: | 5 seconds | 130°C |
| | | 3 seconds | 160°C |
| | Polyester: | 5 seconds | 130°C |
| | Poly/Cotton | 5 seconds | 130°C |
| | Uncoated Nylon: | 5 seconds + 10 | 150°C |
| PRESSURE | Light / Medium | | |
| PEEL | Warm | | |

ACCREDITATIONS



PRINT SETTINGS

Refer to 'Textile Transfer Print Settings' sheet.

CARE INFORMATION

WASH INSIDE OUT - Polyester & Polycotton - 60°C / Cotton & Nylon - 40°C
CAN BE TUMBLE DRIED
DO NOT IRON
STORAGE (Store vertically in a dry room between 15-30°C)

* All force testing has been undertaken using a NEW film blade on a Roland SP300I and a Mimaki CJV150-75. The force will increase with the age of the blade, therefore always test prior to use.

PLEASE NOTE: The sellers and manufacturers maximum obligation shall be to replace any product that has been proven to be defective. Neither the seller nor the manufacturer of Solvent Dark Turbo shall be liable for any injury direct or consequential, arising out of the use of, or inability to use this range. Solvent Dark Turbo has been tested using Kustom Kit garments, when applying to other garment brands results may vary, testing prior to purchase is recommended.